

Flowline

SPECIALISTS IN FLOW MEASUREMENT

[Full Pipe Flows](#)

[Gas Flows](#)

[Steam Flows](#)

[Effluent Flows](#)

[River Flows](#)

[Data Loggers](#)

Flo-gage Range

The Flo-Gage range are direct reading flowmeters with a large easy to read dial calibrated in engineering units (GPM, SCFM, LPM, etc.). Flo-Gage are suitable for measuring water, oil, and most low viscosity liquids as well as compressed air, oxygen, carbon dioxide, nitrogen and many other non-toxic compressed gases. Saturated steam can also be measured up to 120 psig max. The flowmeter is self-contained and complete. Available in threaded and flanged connection.

Flo-Gage Compact Direct reading Orifice Plate Flowmeters for Saturated Steam

Saturated steam flow meters are made of sturdy all metal construction and inverted aluminium housing for horizontal piping. Steam pressures are limited to 120# saturated. Steam flow meters can be ordered in either a threaded connection series 7000 or wafer style connection series 8000.

Standard Specifications:

Accuracy: $\pm 3\%$ F.S.

Repeatability: $\pm 1\%$ F.S.

Pressure Max.: 120 psig (8.43 kg/cm²)

Pressure Min.: 10 psig (0.67 kg/cm²)

Temp. Max.: 350 °F (176.6°C)



Flowline Mfg Ltd. 58 Tewin Road, Welwyn Garden City, AL7 1BD United Kingdom.

Telephone 01707 375564, Email sales@flowline.co.uk Website www.flowline.co.uk

Registered in England No. 1999031, Registered office 20A Plantagenet Road, New Barnet, Herts, EN5 5JG